GLV109-06	Autarco	XLX-MIII	
C10/26 - DECLAR. GLV ed2.1.2 (12/20	ATION OF CONFORM	NTY for power-generating units	Superarid
or the application o the Synergrid prescr	of annex D "Technical basi Piption C10/11 ed2.1 (01	ic requirements regarding the power-generation units" of /09/2019)	- Synergrid

iThe I				
The undersigned,	Manufacturer:	Autarco Group B.V.	Represented by:	Fleur Leloup
	Address:	Torenallee 20	Country:	The Netherlands
		5617 BC Eindhoven	email:	fleur.leloup@autarco.com
L		The Netherlands	Telephone:	00-31623517552

Hereby declares that each production unit completed in the list in tab 'list of power-generating units' of this homologation application complies with the following conditions:

- 1. The power-generating unit complies with the relevant requirements set out in annex D "Technical basic requirements regarding the power-generation units" of the Synergrid prescription C10/11 ed2.1 (01/09/2019).
- 2. In order to substantiate this, a separate technical file has been submitted at least for each separate product series of the 'C10/26 list of power-generating units' of this homologation application. Each technical file shall be drawn up on the basis of a checklist Annex D, duly and correctly completed by the manufacturer, accompanied by all the required proof of conformity.
 - 2.1 For technical requirements for which the required proof of conformity (column J in checklist annex D) is a declaration of honour by the manufacturer, the manufacturer declares by signing and dating this declaration of conformity the correctness of the information (conform / not conform / not applicable) provided by him or her in columns K, L and M of this checklist.
 - 2.2. For technical requirements for which the required proof of conformity (column J in checklist Annex D) is a test report or a certificate, the necessary test reports and/or certificates are technical file:
 - Certificates have been issued by an EN 45011 (or ISO 17065:2012) certification body accredited for these materials.
 - Test reports have been established by an ISO 17025:2005 or ISO 17065:2012 laboratory accredited for these tests.
 - 2.3 A list of the document references or the certificates of conformity referred to in the checklist Annex D is also available in the technical file.

Eindhoven, The Netherlands Done at: Homologated by Synergrid op-On: Stamp Synergrid & signature: 10VEN, The Netherlands (stamp manufacturer & signature) +31 (0) 85 303 13 42 T.V.A./B.Y.W : BE 0402,958,091 Transition period till 01/05/2020 (see exceptions in chapter 3 of C10/11 ed 2.1 (01/09/2019)):

If at the time of submission of this homologation application it is not yet possible to submit all the necessary certificates and/or test reports (exception 3), or that the units do not yet have all the required characteristics (exceptions 1 and 2), a temporary homologation may be granted. All necessary certificates and/or test reports must be in the possession of Synergrid at the latest on 30/04/2020 in order to obtain a final homologation. if this is not the case, the temporary C10/26 homologation will be withdrawn.

POWER-GENERATING UNITS TO BE HOMOLOGATED FOR LIST C10/26 ACCORDING TO THE REQUIREMENTS OF ANNEX D OF THE TECHNICAL PRESCRIPTION C10/11 ed2.1 (01/09/2019) 2. C10/26 list with power-generating units in accordance with annex D of C10/11 ed2.1 (01/09/2019) [GLV109-06 | Autarco | XIX-MIII

GLV109-06 Autarco checklist ed 2.1.2 (12/2019)

	2	3	4	5	6	7	8	9	10	1		- 1	1		σľ		12			-	1	3		14	15
		-	-			ultable for) energy age:	POWER			ADDITIONAL CHARACTERISTICS					CS	LIMITATIONS				APPLICATION				Synergrid approval	
					Name and refer	ance of the power system				D.3	3	D.4.1	D.0.2	D.7.2	0	0.7.1	043	291	0	T	Π				
SYMERGRID reference number (GLYXXX-yy-ZXXX)	BRAND NAME	Name of the product SERIES	REFERENCE of the model / type of the unit	FIRMWARE VERSION	power centrol system type EnFluMi	other power control system	P_, rated (active) power (W)	S _{tim} maximum apparent power (VA)	1-phase or 3-phase	integrated system	"RG type B ready" = suitable t	additional operating frequency range (51,6 Hz - 82,6 Hz)	power response to	active power reduction P(U)	compliant power control syste	only homologated for "armal por	only homologated for	only homologated for	only homologated as a backu	Wind energy Boler energy	GP (combined heat & power)	Energy atomga	Other	Temporary homologation (expires on 01/05/2020)	Final humologation
3LV109-06-0001	Auterco	XLX Mark III	S2.XLX25000-MIN	V2F (and above)			25.000	27.500	3-phase		1 8	H	\dashv	×	-	-	+	- 15	,	+	H	+	Н		
GLV109-06-0002	Autarco	XLX Mark III	S2.XLX30000-MIII	V2F (and above)		_	30,000	33.000	3-phase	Ë		H	\dashv	x	\dashv	+	+	+	۲	-	H	+	+		
GLV109-06-0003	Autarco	XLX Mark III	S2.XLX33000-MIII	V2F (and above)			33.000	36,300	3-phase	+	\vdash	H	\dashv	х .	\dashv	\dashv	+	+	۲,	+	Н	+	+		
GLV109-06-0004	Autarco	XLX Mark III	S2.XLX36000-MIII	V2F (and above)			36,000	39,600	3-phase	+		H		x	+	\dashv	+	+	۲,	+	Н	+	\forall		
GLV109-08-0005	Autarco	XLX Mark III	S2.XLX40000-MIII	V2F (and above)			40,000	44 000	3.nhose	1	Н	\vdash	\dashv	_	\dashv	+	+	+	+	+	Н	+	+		

EXPLANATIONS FOR THE COMPLETION OF THE TABLE

Column	Tittle	Remarks
		IN the case of a posture noncongation, each 110/26-noncongated power-generating unit is given a unique synatging reterence number:
	SYNERGRID reference number	ion = unique reference or the manufacturer
1	220700000000000000000000000000000000000	yy = serial number of manufacturer pods record sox
	(GLVxx-yy-zzzz)	2222 = unique unit reference for the manufacturer xxx
		More : "GUE" at the internal Supermed abbrevation for Declaration of Conformatic housed on the Dutch word "Cold promote information of
2	Brand name	Brand name under which the unit is marketed on the Belgian market,
	- AW G. 1 C	Name of the product range.
3	Name of the product senes	Note: For each separate product range (or each group of units with common characteristics) a separate checklist according to Appendix D is required (sheet 3) together with the corresponding conformity proof documents.
4	Reference of the model / type	Unique product name or reference. Units of the same product range inust be unequivocally distinguished from each other through this name or reference.
	of the unit	the state of the same product issue a margarate of the same of the
5	Firmware version	Reference of the firmware version of the unit.
6	power control system type	This case is only applicable for unity (suitable for) energy storage, provided with a power control system of type [Influft]: Name and reference of the power control system of type Enfluft.
	EnfluR	Int 2 1 (01/09/2019) 64 1 7 and 62 11 2 1
7	other power control system	This case is only applicable for units (suitable for) energy storage, provided with a power control system of another type than Enf kills: Name and reference of the power control system, compliant to the requirements in C10/11 ec (01/09/2019) § 7.11.2.2
4	P, rated (active) power (W)	Active (electrical) power in W at the terminals of the unit, as stated on the technical sheet / data sheet / brochure and naroeplate.
9	Smax - maximum apparent power (VA)	Maximum apparent (electrical) power at the terminals of the unit, as stated on the certificate / the test report / the technical sheet / data sheet / brochure.
10	1-phase or 3-phase	Indicate whether the unit is single- or three-phase. This characteristic refurs to the unit licelf, not to the nature of the connection to the distribution network to which the unit can be connected.
		In these columns optional additional characteristics of the units are indicated, following the information in checklist annex D and the corresponding technical file,
	Additional characteristics	Put an "X" at each relevant additional characteristic.
11	Additional Characteratics	Note: Only units < 1 MW that are "type 8 ready" may be applied in an installation > 1 MW (installation "type 8" according to the European Network Code RfG). A unit < 1 MW is only "type 8 ready" if it complies with all optional
		properties ticked in column I of the checklist Annex D.
	T	These columns specify limitations of the units to their application in certain types of installations, in accordance with the information in the checklist in annex D and the corresponding technical file.
12	Limitations	Put an "X" to each relevant limitation.
	4204.03001	Indicate the applications for which the unit is suitable.
13	Application	Include an "X" with each application for which the unit can be used.





14	Synergrid approval date Temporary homologation (expires on 01/05/2020)	Date on which the submitted homologation file was approved by Synergrid for a limited period of time. - A temporary homologation is granted if the applicant invokes exceptions in chapter 3 of C10/11 ed.2.1 (01/09/2019) and has not yet submitted all the test reports application (exception 3), or if the units do not yet have all the required properties (exception 3) and 1 and 2). - The expiry date for a temporary homologation is 01/05/2020 - see conditions in chapter 3 of C10/11 ed.2.1 (01/09/2019).	required for a definitive homologation with his homologation
15	Synergrid approval date Final homologation	Dale on which the submitted homologation hie was definitely approved by Synergins. - A final approval will be granted as soon as Synergind has a fully compliant homologation dossier. - A final homologation only remains valid under the following conditions: - No changes that have an influence on the initial approval are made to (the production of) the units. - There is no new edition of prescription CIO/11. - The validity date of the test reports in the technical file submitted for approval has not been exceeded. See also the apportal Sumerand concedure 5.1/01.for homologation of material which is applicable. (1)	SYNERGRID a s.b.lv.z. Galerie Ravensteingalerij BE-1000 Bruxelles/Bruse T.V.A

[11-52/01 Technical specification: procedure for application for homologation and renewal of homologation of materials



