GLV109-05	Autarco	UX-MII
C10/26 - DECLAR GLV ed2.1.2 (12/20	ATION OF CONFORM	ITY for power-generating units

for the application of annex D "Technical basic requirements regarding the power-generation units" of the Synergrid prescription C10/11 ed2.1 (01/09/2019)



The sund !	Manufacturer:	Autarco Group B.V.	Represented by:	Fleur Leloup
	Address:	Torenallee 20	Country:	The Netherlands
		5617 BC, Eindhoven	email:	fleur.leloup@autarco.com
		The Netherlands	Telephone:	0031-853031342

Hereby declares that each production unit completed in the list in tab 'list of power-generating units' of this homologation application complies with the following conditions:

- 1. The power-generating unit complies with the relevant requirements set out in annex D "Technical basic requirements regarding the power-generation units" of the Synergrid prescription C10/11 ed2.1 (01/09/2019).
- 2. In order to substantiate this, a separate technical file has been submitted at least for each separate product series of the 'C10/26 list of power-generating units' of this homologation application. Each technical file shall be drawn up on the basis of a checklist Annex D, duly and correctly completed by the manufacturer, accompanied by all the required proof of conformity.
 - 2.1 For technical requirements for which the required proof of conformity (column J in checklist annex D) is a declaration of honour by the manufacturer, the manufacturer declares by signing and dating this declaration of conformity the correctness of the information (conform / not conform / not applicable) provided by him or her in columns K, L and M of this checklist.
 - 2.2. For technical requirements for which the required proof of conformity (column J in checklist Annex D) is a test report or a certificate, the necessary test reports and/of certificates a technical file:
 - Certificates have been issued by an EN 45011 (or ISO 17065:2012) certification body accredited for these materials.
 - Test reports have been established by an ISO 17025:2005 or ISO 17065:2012 laboratory accredited for these tests,
 - 2.3 A list of the document references or the certificates of conformity referred to in the checklist Annex D is also available in the technical file.

Eindhoven, The Netherlands Done at: Homologated by Synergrid on: On: (stamp manufacturer & signature)

avénsteingalerii 4/2

Transition period till 01/05/2020 (see exceptions in chapter 3 of C10/11 ed 2.1 (01/09/2019));

If at the time of submission of this homologation application it is not yet possible to submit all the necessary certificates and/or test reports (exception 3), or that the units do not yet have all the required characteristics (exceptions 1 and 2), a temporary homologation may be granted. All necessary certificates and/or test reports must be in the possession of Synergrid at the latest on 30/04/2020 in order to obtain a final homologation, if this is not the case, the temporary C10/26 homologation will be withdrawn.

POWER-GENERATING UNITS TO BE HOMOLOGATED FOR LIST C10/26 ACCORDING TO THE REQUIREMENTS OF ANNEX D OF THE TECHNICAL PRESCRIPTION C10/11 ed2.1 (01/09/2019)

2. C10/26 list with power-generating units in accordance with annex D of C10/11 ed2.1 (01/09/2019)

GLV109-05 Autarco UX-MII checklist ed 2.1.2 (12/2019)

1	2	3	4	5	6	7	8	9	10	1	11			12			12			12			12			12			12			12			12			13	1		14	15
						ONLY for units (suitable for) energy storage:				ADD	ADDITIONAL CHARACTERISTICS				s					AP	PLICA	MOITA	V		pproval date																	
					Name and refere					0.3	2	D.4.1	083	773	0.7.1	D.4.3	0.9.1	1		T																						
SYNERGRID reference number (GLVxxx-yy-zzzz)	BRAND NAME	Name of the product SERIES	REFERENCE of the model / type of the unit	FIRMWARE VERSION	power control system type EnFluRi	other power control system	P _{sc.} , rated (active) power (W)	S _{max} maximum apparent power (VA)	1-phase or 3-phase	integrated automatic separation system	"RfG type B ready" = suitable for use installation ≥ 1MW	additional operating frequency range (51.5 Hz - 52.5 Hz)	active power reduction (O)	ded (e.g. EnFluRI)	generating installations" compliant power control system	connection to HV-network	only homologated for	syste	only homologated as a backup power	find energy	CHP (combined heat & power)	Energy storage	Other	Temporary homologation (expires on 01/05/2020)	Final homologation																	
GLV109-05- 0001	Autarco	UX Mark II	S2 UX50000(S)-MII	VD6 (and above)			50000	55000	3-phase				,						x																							
GLV109-05- 0002	Autarco	UX Mark II	S2 UX60000(S)-MII	VD6 (and above)			60000	66000	3-phase				,						×																							
				-		-	-	-	-	-		_		-	_	-		-		-		-			-																	
			-			-			 	-			+	+		+	+	+	+	+		+	+		 																	
***************************************					-									1																												
			1	 	 	-	-		-	-		-	-	-	+	-	+	-	+	+	-	-	+		-																	
													-	+			-				SY	NE	RE	RID a.	s.b.lv																	
			-	1	1	1	_	-		1			1		-		1	+	_					venst																		

EXPLANATIONS FOR THE COMPLETION OF THE TABLE

Column	Title	Remarks
		in the case of a positive homologation, each C10/26-homologated power-generating unit is given a unique Synergrid reference number:
	SYNERGRID reference	xxx = unique reference or the manufacturer
1	number	yy = serial number of manufacturer xxx's record xxx
	(GLVxxx-yy-zzzz)	zzzz = unique unit reference for the manufacturer xxx
		Note: "GLV" is the internal Synergrid-obbreviation for Declaration of Conformity, based on the Dutch word "Gelijkvormigheidsverklaring".
2	Brand name	Brand name under which the unit is marketed on the Belgian market,
		Name of the product range.
2	Name of the product series	Note: For each separate product range (or each group of units with common characteristics) a separate checklist according to Appendix D is required (sheet 3) together with the corresponding conformity
,		proof documents.
	Reference of the model /	Unique product name or reference. Units of the same product range must be unequivocally distinguished from each other through this name or reference.
4	type of the unit	Onique product name of reference, onicos die same protesting.
5	Firmware version	Reference of the firmware version of the unit.
	power control system type	This case is only applicable for units (suitable for) energy storage, provided with a power control system of type Enfluit: Name and reference of the power control system of type Enfluit, compliant to the
6		requirements in C10/11 ed2.1 (01/09/2019) §4 1.7 and §7.11.2.1
		This case is only applicable for units (suitable for) energy storage, provided with a power control system of another type than EnFluRi: Name and reference of the power control system, compliant to the
7	other power control system	requirements in C10/11 ed2.1 (01/09/2019) §7.11.2.2
8 Pac, rated (active) power (W)		Active (electrical) power in W at the terminals of the unit, as stated on the technical sheet / data sheet / brochure and nameplate.
		(For photovoltaic Inverters: see also definition in §3.2.5 of IEC 62894 2016-11)
Smax - maximum apparent		Maximum apparent (electrical) power at the terminals of the unit, as stated on the certificate / the test report / the technical sheet / data sheet / brochure.

C10/26 - homologation - 2. list of power-generating units 2.1.2 (12/2019) on the basis of C10/11 ed.2.1 (01/09/2019) - p 1/2



	-	
10	1-phase or 3-phase	Indicate whether the unit is single- or three-phase. This characteristic refers to the unit itself, not to the nature of the connection to the distribution network to which the unit can be connected.
11	Additional characteristics	In these columns optional additional characteristics of the units are indicated, following the information in checklist annex D and the corresponding technical file. Put an "X" at each relevant additional characteristic. Note: Only units < 1 MW that are "type B ready" may be applied in an installation > 1 MW (installation "type B" according to the European Network Code RfG). A unit < 1 MW is only "type B ready" if it complies with all optional properties ticked in column I of the checklist Annex D.
12	Limitations	These columns specify limitations of the units to their application in certain types of installations, in accordance with the information in the checklist in annex D and the corresponding technical file. Put an "X" to each relevant limitation.
13	Application	Indicate the applications for which the unit is suitable. Include an "X" with each application for which the unit can be used.
14	Synergrid approval date Temporary homologation (expires on 01/05/2020)	Date on which the submitted homologation file was approved by Synergrid for a limited period of time. - A temporary homologation is granted if the applicant invokes exceptions in chapter 3 of C10/11 ed2.1 (01/09/2019) and has not yet submitted all the test reports required for a definitive homologation with his homologation application (exception 3), or if the units do not yet have all the required properties (exceptions 1 and 2). - The expiry date for a temporary homologation is 01/05/2020 - see conditions in chapter 3 of C10/11 ed.2.1 (01/09/2019).
15	Synergrid approval date Final homologation	Date on which the submitted homologation file was definitely approved by Synergrid. - A final approval will be granted as soon as Synergrid has a fully compliant homologation dossier. - A final homologation only remains valid under the following conditions: - No changes that have an influence on the initial approval are made to (the production of) the units. - There is no new edition of prescription C10/11. - The validity date of the test reports in the technical file submitted for approval has not been exceeded.

(1) - \$1/01 Technical specification: procedure for application for homologation and renewal of homologation of materials

See also the general Synergrid procedure 51/01 for homologation of material, which is applicable. (1)





