

Compliance Document

No. D 090313 0019 Rev. 00


Holder of Certificate: **Autarco Group BV**
Torenallee 20
5617 BC Eindhoven
THE NETHERLANDS

Product: **Converter**
PV Grid Tied Inverter

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. For details see: www.tuvsud.com/ps-cert

Test report no.: 704092228704-00

Date, 2022-05-16



(Zhengdong Ma)

Compliance Document

No. D 090313 0019 Rev. 00

Model(s): S2.SX700(S)-MII, S2.SX1000(S)-MII, S2.SX1500(S)-MII, S2.SX2000(S)-MII, S2.SX2500(S)-MII, S2.SX3000(S)-MII, S2.SX3600(S)-MII, S2.SX700-MIII, S2.SX1000-MIII, S2.SX1500-MIII, S2.SX2000-MIII, S2.SX2500-MIII, S2.SX3000-MIII, S2.SX3600-MIII.

Parameters:

PV input parameters	
Max. input voltage:	d.c. 600 V (S2.SX700(S)-MII, S2.SX1000(S)-MII, S2.SX1500(S)-MII, S2.SX2000(S)-MII, S2.SX2500(S)-MII, S2.SX3000(S)-MII, S2.SX3600(S)-MII)
Max. input current:	d.c. 11 A (S2.SX700(S)-MII, S2.SX1000(S)-MII, S2.SX1500(S)-MII, S2.SX2000(S)-MII, S2.SX2500(S)-MII, S2.SX3000(S)-MII) d.c. 19 A (S2.SX3600(S)-MII)
Isc PV (absolute maximum)	d.c. 17.2 A (S2.SX700(S)-MII, S2.SX1000(S)-MII, S2.SX1500(S)-MII, S2.SX2000(S)-MII, S2.SX2500(S)-MII, S2.SX3000(S)-MII) d.c.30 A (S2.SX3600(S)-MII)
MPPT voltage range	d.c. 50-500 V (S2.SX700(S)-MII, S2.SX1000(S)-MII, S2.SX1500(S)-MII) d.c. 80-500 V (S2.SX2000(S)-MII, S2.SX2500(S)-MII, S2.SX3000(S)-MII, S2.SX3600(S)-MII)

Compliance Document

No. D 090313 0019 Rev. 00

AC output parameters	
Rated output power	700 W (S2.SX700(S)-MII) 1000 W (S2.SX1000(S)-MII) 1500 W (S2.SX1500(S)-MII) 2000 W (S2.SX2000(S)-MII) 2500 W (S2.SX2500(S)-MII) 3000 W (S2.SX3000(S)-MII) 3600 W (S2.SX3600(S)-MII)
Max. AC output active power	800 W (S2.SX700(S)-MII) 1100 W (S2.SX1000(S)-MII) 1700 W (S2.SX1500(S)-MII) 2200 W (S2.SX2000(S)-MII) 2800 W (S2.SX2500(S)-MII) 3300 W (S2.SX3000(S)-MII) 3600 W (S2.SX3600(S)-MII)
Max. AC output apparent power	800 VA (S2.SX700(S)-MII) 1100 VA (S2.SX1000(S)-MII) 1700 VA (S2.SX1500(S)-MII) 2200 VA (S2.SX2000(S)-MII) 2800 VA (S2.SX2500(S)-MII) 3300 VA (S2.SX3000(S)-MII) 3600 VA (S2.SX3600(S)-MII)
Rated grid voltage	a.c. 230 V
Rated grid frequency	50 Hz
Max. continuous output current	a.c. 4.4 A (S2.SX700(S)-MII) a.c. 5.2 A (S2.SX1000(S)-MII) a.c. 8.1 A (S2.SX1500(S)-MII) a.c. 10.5 A (S2.SX2000(S)-MII) a.c. 13.3 A (S2.SX2500(S)-MII) a.c. 15.7 A (S2.SX3000(S)-MII) a.c. 16 A (S2.SX3600(S)-MII)
Adjustable $\cos(\varphi)$	-0.8...+0.8
Others	
Operating temperature range:	-25 °C...+60 °C
Protective class:	I
Ingress protection:	IP65
Overvoltage category:	PV: II, Main: III
Inverter topology:	Non-isolated



Compliance Document

No. D 090313 0019 Rev. 00

PV input parameters	
Max. input voltage:	d.c. 600 V (S2.SX700-MIII, S2.SX1000-MIII, S2.SX1500-MIII, S2.SX2000-MIII, S2.SX2500-MIII, S2.SX3000-MIII, S2.SX3600-MIII)
Max. input current:	d.c. 14 A (S2.SX700-MIII, S2.SX1000-MIII, S2.SX1500-MIII, S2.SX2000-MIII, S2.SX2500-MIII, S2.SX3000-MIII) d.c. 19 A (S2.SX3600-MIII)
Isc PV (absolute maximum)	d.c. 22 A (S2.SX700-MIII, S2.SX1000-MIII, S2.SX1500-MIII, S2.SX2000-MIII, S2.SX2500-MIII, S2.SX3000-MIII) d.c. 30 A (S2.SX3600-MIII)
MPPT voltage range	d.c. 50-500 V (S2.SX700-MIII, S2.SX1000-MIII, S2.SX1500-MIII) d.c. 80-500 V (S2.SX2000-MIII, S2.SX2500-MIII, S2.SX3000-MIII, S2.SX3600-MIII)

Compliance Document

No. D 090313 0019 Rev. 00

AC output parameters	
Rated output power	700 W (S2.SX700-MIII) 1000 W (S2.SX1000-MIII) 1500 W (S2.SX1500-MIII) 2000 W (S2.SX2000-MIII) 2500 W (S2.SX2500-MIII) 3000 W (S2.SX3000-MIII) 3600 W (S2.SX3600-MIII)
Max. AC output active power	770 W (S2.SX700-MIII) 1100 W (S2.SX1000-MIII) 1650 W (S2.SX1500-MIII) 2200 W (S2.SX2000-MIII) 2750 W (S2.SX2500-MIII) 3300 W (S2.SX3000-MIII) 3600 W (S2.SX3600-MIII)
Max. AC output apparent power	770 VA (S2.SX700-MIII) 1100 VA (S2.SX1000-MIII) 1650 VA (S2.SX1500-MIII) 2200 VA (S2.SX2000-MIII) 2750 VA (S2.SX2500-MIII) 3300 VA (S2.SX3000-MIII) 3600 VA (S2.SX3600-MIII)
Rated grid voltage	a.c. 230 V
Rated grid frequency	50 Hz
Max. continuous output current	a.c. 4.4 A (S2.SX700-MIII) a.c. 5.2 A (S2.SX1000-MIII) a.c. 8.1 A (S2.SX1500-MIII) a.c. 10.5 A (S2.SX2000-MIII) a.c. 13.3 A (S2.SX2500-MIII) a.c. 15.7 A (S2.SX3000-MIII) a.c. 16 A (S2.SX3600-MIII)
Adjustable $\cos(\varphi)$	-0.8...+0.8
Others	
Operating temperature range:	-25°C...+60°C
Protective class:	I
Ingress protection:	IP66
Overtoltage category:	PV: II, Main: III
Inverter topology:	Non-isolated

**Tested
according to:**

UTE C15-712-1:2013
DIN V VDE V 0126-1-1/A1 (VDE V 0126-1-1/A1):2012 (with
national deviation of France: DIN VDE 0126-1-1/A1 VFR 2019)