

LD Mark III

Series solar inverters

The Autarco LD series Mark III inverters offer the latest in grid tied inverter technology. The inverter is a key element in a solar PV power plant and these inverters provide the reliable basis for Autarco's unique kWh guarantee.

- + Eligible for Autarco's insured kWh Guarantee
- + Reduced Fire Risk due to Integrated AFCI
- + Extremely lightweight and silent
- + Wide MPP tracker range
- + Waterproof IP66 enclosure



Quality Certificates


EN 50549-1, EN 61000-6-1/2/3/4 (CE), IEC 62109-1/2
VDE 4105, VDE 0126, C10/11, NTS 631, RD 1699, RD 413




General characteristics

Dimensions (W x H x D)	310 x 563 x 219mm
Net Weight	17.8 - 20kg
Mounting	Wall bracket
Max. site altitude	4000m
IP protection class	IP66
Isolation type	Transformerless
Cooling principle	Intelligent redundant fan-cooling
Noise level, typically	< 20dBA
Product guarantee	5 year standard (10 & 15 year optional)
Consumption monitoring	Optional with meter
Communication interfaces	1 x RS485
Monitoring Options	WiFi, GPRS, 5G and Ethernet
DC switch	Integrated (optionally excluded)
Power Export Limitation	Integrated


Front




Side



Bottom



Bracket



Input characteristics

	S2.LD5000-MIII	S2.LD6000-MIII	S2.LD8000-MIII	S2.LD9000-MIII	S2.LD10000-MIII
Max. PV input power (W)	7500	9000	12000	13500	15000
Max. DC voltage (V)	1100	1100	1100	1100	1100
MPP tracker voltage range (V)	160-1000	160-1000	160-1000	160-1000	160-1000
Start-up DC voltage (V)	180	180	180	180	180
Number of MPP trackers	2	2	2	2	2
Max. DC current per MPPT (A)	16	16	16	16	16
Max. short circuit current (A)	25	25	25	25	25
Number of DC connections per MPPT	1	1	1	1	1
DC connection type	MC4	MC4	MC4	MC4	MC4
Turn on power (W)	10	10	10	10	10

Output characteristics

	Plug-in	Plug-in	Plug-in	Plug-in	Plug-in
Power connection	3-phase	3-phase	3-phase	3-phase	3-phase
Rated AC power (W)	5000	6000	8000	9000	10000
Max. AC power (W)	5500	6600	8800	9900	11000
Rated Grid Voltage (V)	3P/N/PE, 220 V / 380 V, 230 V / 400 V				
Rated Grid Frequency (Hz)	50 Hz / 60 Hz				
Rated AC current (A)	7.6 / 7.2	9.1 / 8.7	12.2 / 11.5	13.7 / 13.0	15.2 / 14.4
Max. AC current (A)	7.9	9.5	12.7	14.3	15.9
Power factor	0.8...1...0.8	0.8...1...0.8	0.8...1...0.8	0.8...1...0.8	0.8...1...0.8
Harmonic distortion (%)	< 2%	< 2%	< 2%	< 2%	< 2%
Night-time power consumption (W)	< 1	< 1	< 1	< 1	< 1
Standby power consumption (W)	6	6	6	6	6

Efficiency

Max. efficiency	98.3 ~ 98.7%
EU efficiency	97.7 ~ 98.1%
MPPT efficiency	> 99.5%

Protection

DC overvoltage protection	Integrated
DC reverse polarity protection	Integrated
Short circuit protection	Integrated
Grid monitoring	Integrated
Residual current detection	Integrated
Insulation resistance monitoring	Integrated
Temperature protection	Integrated
Islanding protection	Integrated
Arc-fault circuit interrupter	Integrated

Other characteristics

Operating temperature range	-25°C to +60°C
Relative humidity range	0% to 100%

