



Product Service

Attestation of Conformity

No. T8B 090313 0051 Rev. 00

Holder of Attestation: Autarco Group BVTorenallee 20
5617 BC Eindhoven
THE NETHERLANDS**Product: Converter
Hybrid Inverter**

This Attestation of Conformity is issued on a voluntary basis in support of the Conformity Assessment Module A of Radio Equipment Directive 2014/53/EU. On the basis of the referenced test reports, the samples of the listed product were found to comply with the essential requirements of the below listed articles in the above-mentioned directive as implemented in the standards used valid at the time the tests were carried out. For the covered requirements of the Article(s) 3.2, 3.3(d) and 3.3(e) only harmonized standards valid at the moment of issuing where used. The used standards cover the essential requirements of the below listed articles of the Radio Equipment Directive as applicable to this product. For details see: www.tuvsud.com/ps-cert

Test report no.: 4812825031200**Date,** 2025-12-23

(Ming Gu)

Page 1 of 10

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. T8B 090313 0051 Rev. 00

Model(s): S2.MH3000-MIII, S2.MH3600-MIII, S2.MH5000-MIII,
S2.MH6000-MIII, S2.MH8000-MIII, S2.MH3000M-MIII,
S2.MH3600M-MIII, S2.MH5000M-MIII,
S2.MH6000M-MIII, S2.MH8000M-MIII,
S2.MH10000M-MIII

Parameters:

Test report No.:	
Article 3.1(a)	701262523201-00 (EN 62109-1, EN 62109-2) 4812825031200C (EN 50663)
Article 3.1(b)	4812825031200A (EN IEC 61000-6-1, EN IEC 61000-6-2, EN IEC 61000-6-3, EN IEC 61000-6-4, EN 55011, EN 62920) 4812825031200B (EN 301 489-1, EN 301 489-17)
Article 3.2	4812825031200C (EN 300 328)

Page 2 of 10

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. T8B 090313 0051 Rev. 00

Model	S2.MH3000-MIII	S2.MH3600-MIII	S2.MH5000-MIII
PV input			
Max. input voltage	500 Vd.c.	500 Vd.c.	500 Vd.c.
MPPT voltage range	90, ..., 435 Vd.c.	90, ..., 435 Vd.c.	90, ..., 435 Vd.c.
Max. input current	2x16 Ad.c.	2x16 Ad.c.	2x16 Ad.c.
Isc PV (absolute maximum)	2x20 Ad.c.	2x20 Ad.c.	2x20 Ad.c.
Battery input			
Battery type	Li-ion/Lead-acid		
Battery voltage range	40, ..., 60 Vd.c.	40, ..., 60 Vd.c.	40, ..., 60 Vd.c.
Max. charge current	70 Ad.c.	80 Ad.c.	112 Ad.c.
Max. discharge current	70 Ad.c.	80 Ad.c.	112 Ad.c.
AC output (Back-up)			
Max. (rated) output power	3000 W	3600 W	5000 W
Nominal output voltage	1/N/PE 220 Va.c., 1/N/PE 230 Va.c.		
Nominal frequency	50/60 Hz		
Max. (rated) output current	13.7 Aa.c.@ 220 Va.c. 13.1 Aa.c.@ 230 Va.c.	16.4 Aa.c.@ 220 Va.c. 15.7 Aa.c.@ 230 Va.c.	22.8 Aa.c.@ 220 Va.c. 21.8 Aa.c.@ 230 Va.c.
AC output (Grid side)			
Max. (rated) apparent output power	3000 VA	3600 VA	5000 VA
Nominal output voltage	1/N/PE 220 Va.c., 1/N/PE 230 Va.c.		
Nominal frequency	50/60 Hz		
Max. (rated) output current	13.7 Aa.c.@ 220 Va.c. 13.1 Aa.c.@ 230 Va.c.	16.4 Aa.c.@ 220 Va.c. 15.7 Aa.c.@ 230 Va.c.	22.8 Aa.c.@ 220 Va.c. 21.8 Aa.c.@ 230 Va.c.
AC input			
Nominal voltage	1/N/PE 220 Va.c., 1/N/PE 230 Va.c.		
Max. (rated) continuous current	21 Aa.c.@ 220 Va.c. 20 Aa.c.@ 230 Va.c.	25 Aa.c.@ 220 Va.c. 24 Aa.c.@ 230 Va.c.	32 Aa.c.@ 220 Va.c. 31 Aa.c.@ 230 Va.c.
Nominal frequency	50/60 Hz		
General parameters			
Power factor range	-0.8, ..., 1, ..., +0.8		
Protective class	I		
Ingress protection	IP66		
Operating temperature range	-40°C, ..., +60 °C		

Page 3 of 10

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Attestation of Conformity

No. T8B 090313 0051 Rev. 00

Model	S2.MH6000-MIII	S2.MH8000-MIII
PV input		
Max. input voltage	500 Vd.c.	500 Vd.c.
MPPT voltage range	90, ..., 435 Vd.c.	90, ..., 435 Vd.c.
Max. input current	2x16 Ad.c.	2x32 Ad.c.
Isc PV (absolute maximum)	2x20 Ad.c.	2x40 Ad.c.
Battery input		
Battery type	Li-ion/Lead-acid	
Battery voltage range	40, ..., 60 Vd.c.	40, ..., 60 Vd.c.
Max. charge current	135 Ad.c.	190 Ad.c.
Max. discharge current	135 Ad.c.	190 Ad.c.
AC output (Back-up)		
Max./rated output power	6000 W	8000 W
Nominal output voltage	1/N/PE 220 Va.c., 1/N/PE 230 Va.c.	
Nominal frequency	50/60 Hz	
Max. (rated) output current	27.3 Aa.c.@ 220 Va.c. 26.1 Aa.c.@ 230 Va.c.	36.4 Aa.c.@ 220 Va.c. 34.8 Aa.c.@ 230 Va.c.
AC output (Grid side)		
Max. (rated) apparent output power	6000 VA	8000 VA
Nominal output voltage	1/N/PE 220 Va.c., 1/N/PE 230 Va.c.	
Nominal frequency	50/60 Hz	
Max. (rated) output current	27.3 Aa.c.@ 220 Va.c. 26.1 Aa.c.@ 230 Va.c.	36.4 Aa.c.@ 220 Va.c. 34.8 Aa.c.@ 230 Va.c.
AC input		
Nominal voltage	1/N/PE 220 Va.c., 1/N/PE 230 Va.c.	
Max. (rated) continuous current	40 Aa.c. @ 220 Va.c. 39 Aa.c.@ 230 Va.c.	50 Aa.c.@ 220 Va.c. 50 Aa.c.@ 230 Va.c.
Nominal frequency	50/60 Hz	
General parameters		
Power factor range	-0.8, ..., 1, ..., +0.8	
Protective class	I	
Ingress protection	IP66	
Operating temperature range	-40°C, ..., +60 °C	



Product Service

Attestation of Conformity

No. T8B 090313 0051 Rev. 00

Model	S2.MH3000M-MIII	S2.MH3600M-MIII
PV input		
Max. input voltage	500 Vd.c.	
MPPT voltage range	90, ..., 435 Vd.c.	90, ..., 435 Vd.c.
Max. input current	2x21 Ad.c.	2x21 Ad.c.
Isc PV (absolute maximum)	2x24Ad.c.	2x24 Ad.c.
MPPT number/max input strings number	2/2	2/2
Battery input		
Battery type	Li-ion / Lead-acid	
Battery voltage range	40, ..., 60 Vd.c.	40, ..., 60 Vd.c.
Max. charge current	70 Ad.c.	80 Ad.c.
Max. discharge current	70 Ad.c.	80 Ad.c.
AC output (Back-up)		
Max. (rated) output power	3000 W	3600 W
Nominal output voltage	1/N/PE 220 Va.c. 1/N/PE 230 Va.c.	
Nominal frequency	50 / 60 Hz	
Max. (rated) output current	13.7 Aa.c.@ 220 Va.c. 13.1 Aa.c.@ 230 Va.c.	16.4 Aa.c.@ 220 Va.c. 15.7 Aa.c.@ 230 Va.c.
AC output (Grid side)		
Max. (rated) apparent output power	3000 VA	3600 VA
Nominal output voltage	1/N/PE 220 Va.c. 1/N/PE 230 Va.c.	
Nominal frequency	50 / 60 Hz	
Max. (rated) output current	13.7 Aa.c.@ 220 Va.c. 13.1 Aa.c.@ 230 Va.c.	16.4 Aa.c.@ 220 Va.c. 15.7 Aa.c.@ 230 Va.c.
AC input		
Nominal voltage	1/N/PE 220 Va.c. 1/N/PE 230 Va.c.	
Max. (rated) continuous current	21 Aa.c.@ 220 Va.c. 20 Aa.c.@ 230 Va.c.	25 Aa.c.@ 220 Va.c. 24 Aa.c.@ 230 Va.c.
Nominal frequency	50 / 60 Hz	
Power factor range	-0.8, ..., 1, ..., +0.8	
Protective class	I	

Page 5 of 10

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. T8B 090313 0051 Rev. 00

Ingress protection	IP66
Operating temperature range	-40°C, ..., +60 °C

Page 6 of 10

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Attestation of Conformity

No. T8B 090313 0051 Rev. 00

Model	S2.MH5000M-MIII	S2.MH6000M-MIII	S2.MH8000M-MIII
PV input			
Max. input voltage	500 Vd.c.		
MPPT voltage range	90, ..., 435 Vd.c.		
Max. input current	2x21 Ad.c.	2x21 Ad.c.	2x42 Ad.c.
Isc PV (absolute maximum)	2x24 Ad.c.	2x24 Ad.c.	2x48 Ad.c.
MPPT number/max input strings number	2/2	2/2	2/4
Battery input			
Battery type	Li-ion / Lead-acid		
Battery voltage range	40, ..., 60 Vd.c.		
Max. charge current	112 Ad.c.	135 Ad.c.	190 Ad.c.
Max. discharge current	112 Ad.c.	135 Ad.c.	190 Ad.c.
AC output (Back-up)			
Max. (rated) output power	5000 W	6000 W	8000 W
Nominal output voltage	1/N/PE 220 Va.c. 1/N/PE 230 Va.c.		
Nominal frequency	50 / 60 Hz		
Max./rated output current	22.8 Aa.c.@ 220 Va.c. 21.8 Aa.c.@ 230 Va.c.	27.3 Aa.c.@ 220 Va.c. 26.1 Aa.c.@ 230 Va.c.	36.4 Aa.c.@ 220 Va.c. 34.8Aa.c.@ 230 Va.c.
AC output (Grid side)			
Max. (rated) apparent output power	5000 VA	6000 VA	8000 VA
Nominal output voltage	1/N/PE 220 Va.c. 1/N/PE 230 Va.c.		
Nominal frequency	50 / 60 Hz		
Max. (rated) output current	22.8 Aa.c.@ 220 Va.c. 21.8 Aa.c.@ 230 Va.c.	27.3 Aa.c.@ 220 Va.c. 26.1 Aa.c.@ 230 Va.c.	36.4 Aa.c.@ 220 Va.c. 34.8 Aa.c.@ 230 Va.c.
AC input			
Nominal voltage	1/N/PE 220 Va.c. 1/N/PE 230 Va.c.		
Max. (rated) continuous current	32 Aa.c.@ 220 Va.c. 31 Aa.c.@ 230 Va.c.	40 Aa.c.@ 220 Va.c. 39 Aa.c.@ 230 Va.c.	50 Aa.c.@ 220 Va.c. 50 Aa.c.@ 230 Va.c.
Nominal frequency	50 / 60 Hz		

Page 7 of 10

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. T8B 090313 0051 Rev. 00

Power factor range	-0.8, ..., 1, ..., +0.8
Protective class	I
Ingress protection	IP66
Operating temperature range	-40°C, ..., +60 °C

Page 8 of 10

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Attestation of Conformity

No. T8B 090313 0051 Rev. 00

Model	S2.MH10000M-MIII
PV input	
Max. input voltage	500 Vd.c.
MPPT voltage range	90, ..., 435 Vd.c.
Max. input current	2x42 Ad.c.
Isc PV (absolute maximum)	2x48 Ad.c.
MPPT number/max input strings number	2/4
Battery input	
Battery type	Li-ion / Lead-acid
Battery voltage range	40, ..., 60 Vd.c.
Max. charge current	210 Ad.c.
Max. discharge current	210 Ad.c.
AC output (Back-up)	
Max. (rated) output power	10000 W
Nominal output voltage	1/N/PE 220 Va.c. 1/N/PE 230 Va.c.
Nominal frequency	50 / 60 Hz
Max./rated output current	45.5 Aa.c.@ 220 Va.c. 43.5 Aa.c.@ 230 Va.c.
AC output (Grid side)	
Max. (rated) apparent output power	10000 VA
Nominal output voltage	1/N/PE 220 Va.c. 1/N/PE 230 Va.c.
Nominal frequency	50 / 60 Hz
Max. (rated) output current	45.5 Aa.c.@ 220 Va.c. 43.5 Aa.c.@ 230 Va.c.
AC input	
Nominal voltage	1/N/PE 220 Va.c. 1/N/PE 230 Va.c.
Max. (rated) continuous current	65 Aa.c.@ 220 Va.c. 65 Aa.c.@ 230 Va.c.
Nominal frequency	50 / 60 Hz
Power factor range	-0.8, ..., 1, ..., +0.8
Protective class	I
Ingress protection	IP66
Operating temperature range	-40°C, ..., +60 °C

Page 9 of 10

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. T8B 090313 0051 Rev. 00

**Tested
according to:**

EN IEC 61000-6-1:2019
EN IEC 61000-6-2:2019
EN IEC 61000-6-3:2021
EN IEC 61000-6-4:2019
EN 55011:2016/A2:2021
EN 62920:2017/A1:2021
EN 301 489-1 V2.2.3:2019
EN 301 489-17 V3.3.1:2024
EN 300 328 V2.2.2:2019
EN 50663:2017
EN 62109-1:2010
EN 62109-2:2011

Page 10 of 10

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.